

BL2-58

COMPACT & PORTABLE

Features

- Available with Li-ion battery or AC adapter
- 80mm/sec. printing speed
- Horizontal or wall-mount installation
- Drop-in paper loading
- Black or white case color
- Available for use with label paper (option)



BL2-58

Features

Small footprint and lightweight
 Available with Li-ion battery or AC adapter
 80mm/sec. high printing speed
 Drop-in paper loading
 Available for use with label paper (option)
 Horizontal or wall-mount installation
 Black or white case color

Applications

Receipt and ticket
 Medical instruments
 Label
 Coin-counter
 Create Card
 Test instruments

Accessories

Paper roll
 AC adapter



Drop-in paper loading



Printing method	Direct line thermal
Resolution	203dpi (8dots/mm)
Number of dots	384dots
Paper width/ Printing width	58mm/48mm
Printing speed	Max.80mm/ sec
Interface	Serial(RS232C), Parallel, USB
Character font (W x H)	Font A : 12 x 24dots Font B : 8 x 16dots
Character dimensions (W x H)	Font A : 1.5 x 3.0mm Font B : 1.0 x 2.0mm
Number of columns	32 (Font A) 48 (Font B)
Character type	Alphanumeric, International, PC-437/850/852/857/858/863/865/866/WPC1252 Katakana
User-defined logo/ Characters	User-defined logo and Characters can be registered in flash memory
Barcode types	JAN8/13, CODE39/128, ITF, CODABAR, UPC-E/A 2D Barcode (Options) : QR, Maxcode, PDF417, DataMatrix
Input buffer	8k bytes
Emulation	ECS/POS conformity
Power supply	AC adapter : AC100/120/240V±10% 50/60Hz Battery : Rechargeable Li-ion (7.4V/ 2500mAH)
Operating condition	-10 to 50 °C, 10 to 85%RH (Non condensation)
Storage condition	-20 to 60 °C, 10 to 90%RH (Non condensation)
Reliability	Wear resistance : 50Km Pulse resistance, 100 million pulse
Dimensions	93(W) x 125(D) x 70(H)mm
Mass	Approx. 250g (Without paper roll and battery)
Safety standards	VCCI, CE, FCC
Options	Li-ion battery pack, 2D barcode, Label version, Interface cable

*Windows is registered trademark of Microsoft Corporation in the United States and other countries.

*ECS/POS is registered trademark of Seiko Epson Corporation.

*All specifications are subject to change without notice.

Distributed by



SANEI ELECTRIC INC.

www.sanei-elec.co.jp

Headquarters :

2-61-1 Ikebukuro, Toshima-ku, Tokyo 171-0014, Japan

Phone: 81-3-3986-1188 Fax: 81-3-3988-5876

