

Uniquely creative, uniquely responsive to your needs.

MOBILE PRINTER

SM2-41

4" MOBILE LABEL PRINTER

Features

- 150mm/sec. printing speed
- Drop-in paper loading system
- Robust body
- Receipt and Peel-off model available
- Various interface (Serial, USB, IrDA, BT and WiFi)
- Energy saving system (Auto power off)
- Workable for battery and AC adapter



SM2-41L(Peel-off)



SM2-41(Receipt)



SANEI ELECTRIC INC.

Phone 03-3986-1188 www.sanei-elec.co.jp

SM2-41

Features

- High speed printing at 150mm/sec.
- Drop-in paper loading and large capacity paper bucket
- Adjustable paper width (50mm to 115mm)
- Various interface (Serial, USB, IrDA, BT and WiFi)
- Large battery capacity
- Receipt and Peel-off model available
- Rugged drop resistant design

Applications

- Logistics (Barcode label)
- Receipt and Ticket
- Medical and Inspection label
- Maintenance and Field service

Accessories

- AC adapter
- Li-ion battery
- Shoulder strap



SM2-41(Receipt)

Fanfold paper

SM2-41L(Peel-off)

Model	Peel-off model	Receipt model
Printing method	Direct line thermal	
Resolution	203dpi (8dot/mm)	
Number of dots	Max.832dots/mm	
Printing width	Max.104mm	
Printing speed	Max.150mm/sec. (Peel-off mode : Max.80mm/sec.)	Max.150mm/sec.
Paper	Style	Label paper/Receipt paper
	Type	Roll paper/Fanfold paper
	Width	50 to 115mm
	OD	Max. ϕ 58mm
	Thickness	0.059 to 0.16mm
Character font	9x16, 12x24	
Character type	Alphanumeric, PC437/850/852/857/858/860/863/865/866, WPC1252	
Peel-off operation	Equipped	None
Tear bar	Plastic	Metal
Paper sensor	Black mark, Label gap, Peel-off	Black mark, Label gap
Paper loading	Drop-in paper loading	
Interface	RS232C+USB2.0, IrDA, BT / WiFi (option)	
Emulation	ESC/POS conformity, Label mode	
Barcode	UPC-A/E, JAN 13/8, CODE 39, ITF, CODA BAR, CODE 93, QR code/PDF417	
Power supply	Li-ion rechargeable battery (14.8V/2200mAh) / AC adapter	
Battery charge	Internal battery charger	
Paper guide	Adjustable paper guide at free position	
Reliability	Thermal head : 100Km/100million pauses (at receipt paper)	
Fall impact resistance	1m	
Operating condition	-15 to 50°C	
Dimensions	157(W)x138.6(D)x67(H)mm	
Weight	Approx. 780g (included battery, without roll paper)	
Safety standards	VCCI, CE, FCC	

*ESC/POS is registered trademark of Seiko Epson Corporation.

*All specifications are subject to change without notice.

Distributed by

 **SANEI ELECTRIC INC.**
www.sanei-elec.co.jp

Headquarters :

5F, Taisou-Ikebukuro Building, 2-61-1 Ikebukuro, Toshima-ku, Tokyo 171-0014, Japan
Phone: 81-3-3986-1188 Fax: 81-3-3988-5876

